



Bo Ming Scaffolding (H.K.) Limited 寶銘棚架(香港)有限公司



3488 3860



3488 3861



bmskh.sales@gmail.com



www.bmskh.hk



Trade King 730 Aluminium Scaffold Tower Tested and Certified to EN 1004-1:2020

Tower Dimension : 0.73m(W) x 1.55m(L) x 3.2m(H)
Max. Platform Height : 2.2m, Max. Working Height : 4.2m

Safety Working Load :
Platform - 230 kg when load uniformly distributed

Item	Description	Qty.
1.	Castor Wheel 150mm dia. W/Adj. Leg 150mm 膠輪連調節槽	4
2.	730 4 Rung Frame 0.73m x 1.0m 730 4 橫梯架 0.73m x 1.0m	2
3.	730 6 Rung Foldable Base Unit 730 6 橫摺合底架	-
4.	730 8 Rung Frame 0.73m x 2.0m 730 8 橫架 0.73m x 2.0m	2
5.	Trapdoor Platform 0.6m x 1.55m 半門踏板 0.6m x 1.55m	1
6.	Horizontal Brace 1550 (Red) 橫拉杆 1.55m (紅色)	6
7.	Diagonal Brace 1700 (Blue) 斜拉杆 1.7m (藍色)	4
8.	Wooden Toeboard Set 0.6m x 1.55m 踢腳板組合 0.6m x 1.55m	1
9.	Fixed Outrigger 固定斜撐	4
10.	Telescopic Outrigger 伸縮斜撐	-

Scale : NTS

Ref. : TK730-3200

Weight : approx. 79.3 kg

